# HANDLES - L & T STYLES

### No. 5655-X


Malleable drop handle for padlock.

### No. 5655-SSX

Same as 5655-X except made of 300 Series stainless steel for superior corrosion resistance.

## **No. 40-5655-12** Gasket .062" thick.





This attractive series provides the user with the ability to padlock the handles for security.

Designed to be used with most multipoint latches which use a 5/16" square drive mechanism.

- Ideal in tough corrosive environments.
- Easy to install.


### No. 3-5625

Same as 5655 Series except has 2.50" Shank with 1" threaded.

# No. 5655-SSX (stainless) Finish: Bright Polish Weight: .91 lbs. 22 DIA 3 PLACES 3.25 6.00 1.65 3.25

### No. 46-5655-SSX

Same as 5655-SSX stainless steel drop handle except furnished with (3) 1/4"-20 mounting studs and threaded 3/8"-16 UNC shank.



### Available malleable options. Other options available.

No.	Variations
34-5655-50X 43-5655	3-1/2" threaded shank without escutcheon Same as 5655-X except with 3 (1/4"-20) mounting studs
48-5655-X	Same as 43-5655 except threaded shank
77-5655-50X	2-1/2" partially threaded shank without escutcheon
77-5655-X	Same as 77-5655-50X except has escutcheon with 3 (1/4"-20) mounting studs
77-5655-XU	Same as above except shipped with gasket (loose)

### Available stainless steel options. Other options available.

No.	Variations
5655-SSX	3-1/4" nonthreaded shank with 3 mounting holes in escutcheon
44-5655-SSX	Same as 5655-SSX except has 3 (1/4"-20) mounting studs
45-5655-SSX	Same as 5655-SSX except threaded shank
47-5655-SSX	Same as 44-5655-SSX except shipped with gasket (loose)
48-5655-SSX	Same as 47-5655-SSC except threaded shank