TOOL BOX LATCHES

No. 457-501
Designed to be used with truck toolboxes or storage containers. Also available in nonlocking **No. 3-472-SS.** Standard features are four mounting holes, stainless steel paddle and receptacle. All other parts are carbon steel, zinc-plated. Unit weights: 3-471-SS (.59 lbs.); 3-472-SS (.5 lbs.).





No. 471-55X
Rod Adapter



SUGGESTED CUTOUT

No. 18-471-SS
Same as 3-471-SS except includes guide plate to help align the striker to the latch. Also available in **No. 18-472-SS** nonlocking. Unit weight: .67 lbs.





No. 3-461-SS
Ideal for toolbox lids or compartment doors. Features a three-stage notched plunger designed for varying depths of engagement, stainless steel paddle and receptacle, zinc die cast plunger, stainless steel springs, and black polylube plated carbon steel components on plunger mechanism and bracket. Available in nonlocking **(No. 3-462-SSL).** Unit weights: Locking .82 lbs., nonlocking .74 lbs. To be used in conjunction with Part No. 4618. Rod adapter available **No. 471-55XN.**



Patented





SUGGESTED CUTOUT

No. 4618
To be used in conjunction with 461 or 462 Series. Striker bracket made of black polylube plated carbon steel bracket, zinc-plated spring clip, and aluminum channel for easy welding (optional sizes available). Features up to 3/8" horizontal adjustment. Can also be used with push button Series **No. 862-R/872-R.**

Patented

No. 4618-50
Same as 4618 except without aluminum base.